



NATIONWIDE PLASTICS, INC.

The Authority on Plastics Manufacturing and Distribution



ABS

ABS (CYCOLAC)

ABS, acrylonitrile-butadien-styrene, trade name Cycolac from General Electric, machines well for production or prototype parts. The general purpose ABS grade exhibits good mechanical properties, resistance to chlorine, and a heat deflection temperature of 210 degrees F at 264 temperature (300 degrees F) psi. Black and natural rod are standard. Special ABS grades offered by G.E. may be available on custom quotation.

DIA.	LB/FT
1/4"	0.023
3/8"	0.051
1/2"	0.09
5/8"	0.141
3/4"	0.203
7/8"	0.276
1"	0.361
1 1/4"	0.564
1 1/2"	0.812
1 3/4"	1.11
2"	1.44
2 1/2"	2.26
3"	3.25
3 1/2"	4.42
4"	5.77
5"	9.02
5 1/2"	10.92
6"	12.99

Dallas, Texas (Corporate Offices)
Houston, Texas
Brandon, Mississippi

phone 800-782-1836 / 214-239-3870
phone 800-282-4388 / 713-979-0660
phone 800-457-8623 / 601-825-7919

fax 214-239-3871
fax 713-979-0664
fax 601-825-7109