



NATIONWIDE PLASTICS, INC.

The Authority on Plastics Manufacturing and Distribution



NORYL

NORYL®

Noryl®, made by General Electric, comes in rod and slab in several formulations. Noryl® EN265, Black, contains a self-extinguishing additive. Glass reinforced formulation, GFN3 (30% glass) and SE1 GFN3 (30% glass with self-extinguishing additive) are available in standard grey. Custom colors are available. Overall excellent physical properties, low moisture absorption, heat resistance of 265 degrees F at 264psi combine to make Noryl® a truly high performance material but at very cost effective rates. Parts are easily machined to fill a variety of needs. Used in appliances, liquid handling equipment, and numerous other applications, Noryl® serves many industries. Noryl® is attacked by petroleum products, so knowing the environment which the Noryl® part will be exposed to is vital.

DIA.	LB/FT SE- 1GFN3	LB/FT EN265
3/8"	0.065	0.051
1/2"	0.116	0.09
5/8"	0.18	0.141
3/4"	0.259	0.203
7/8"	0.35	0.276
1"	0.462	0.361
1 1/8"	0.585	0.457
1 1/4"	0.721	0.564
1 1/2"	1.03	0.812
1 3/4"	1.41	1.105
2"	1.85	1.444
2 1/4"	2.34	1.827
2 1/2"	2.89	2.256
2 3/4"	3.49	2.73
3"	4.16	3.249
3 1/2"	5.66	4.422
4"	7.39	5.776
4 1/2"	9.35	7.31
5"	11.55	9.024
6"	16.63	12.995

Dallas, Texas (Corporate Offices)
Houston, Texas
Brandon, Mississippi

phone 800-782-1836 / 214-239-3870
phone 800-282-4388 / 713-979-0660
phone 800-457-8623 / 601-825-7919

fax 214-239-3871
fax 713-979-0664
fax 601-825-7109