



NATIONWIDE PLASTICS, INC.

The Authority on Plastics Manufacturing and Distribution



Material Safety Data Sheet

Product Name: **NylaRide**

Synonyms: **Nylon 66/6 (impact modified)**

NYLARIDE

Composition / Information on Ingredients

Material	%	TLV	PEL
Nylon 6/6	40-80	N/A	N/A
Nylon 6	20-60	N/A	N/A
Inorganic Pigment	1% or less	N/A	N/A

Physical and Chemical Properties

Melting Point: 230-245°C
 Vapor Pressure: N/A
 Vapor Density: N/A
 Solubility in Water: Not Soluble
 PH: N/A
 Specific Gravity: 1.10
 % Volatile By Volume: N/A
 Appearance and Odor: Granular, slight to no odor

Fire and Explosion Hazards

Flashpoint: >400
 Auto Ignition Temperature: None available
 Flammable Limits (STP): N/A

Extinguishing Media: Use water fog, foam, CO₂ or dry chemicals

Special Fire Fighting Protective Equipment: Firefighters should be equipped with self-contained breathing apparatus and turn-out gear

Unusual Fire and Explosion Hazards: Molten plastics, dust can cause explosion hazards.

Stability and Reactivity

Stability: Stable

Incompatibility: Strong oxidizing agents, acids and bases
 Hazardous Decomposition Products: CO₂, Carbon Monoxide, HCN, CO and NH₃.

Hazardous Polymerization: Will not occur

Material Safety Data Sheet

Solus Industrial Innovations, LLC.
Copyright ©2002 All rights reserved. 4/02



Dallas, Texas (Corporate Offices)
 Houston, Texas
 Brandon, Mississippi

phone 800-782-1836 / 214-239-3870
 phone 800-282-4388 / 713-979-0660
 phone 800-457-8623 / 601-825-7919

fax 214-239-3871
 fax 713-979-0664
 fax 601-825-7109